

JAGRO Rotary Tiller



SALIENT FEATURES & BENEFITS



Heavy duty Multi-Speed gear box with 13x23 Crown-Pinion



Best in Class Trailing Board Design for long lasting operations.



Robust main frame with a double pipe structure for extra strength.

Perfect for hard soil conditions, equipped with a heavy-duty multi-speed gearbox, this versatile rotary tiller removes and mixes crop residues, pulverizes, and levels the soil simultaneously.

Technical Specifications

Size	No. of	Working Width	Frame width	Total width	Weight	Tractor	PTO	Blade	Gear Box
	Blaues	B to B (IIIIII)	(mm)	(mm)	(kg)	пр	(ipiii)	туре	Вох
4	30	1188	1288	1470	427	30-35	540	L	Multi-Speed
5	36	1424	1524	1705	450	35-40	540	L	Multi-Speed
5.5	42	1585	1685	1865	475	40-45	540	L	Multi-Speed
6	42	1805	1905	2085	480	45-50	540	L	Multi-Speed
6	48	1805	1905	2085	505	45-50	540	L	Multi-Speed
7	48	2000	2100	2280	530	50-55	540	L	Multi-Speed
7	54	2000	2100	2280	535	50-55	540	L	Multi-Speed
8	54	2205	2305	2485	560	55-60	540	L	Multi-Speed
8	60	2205	2305	2485	570	55-60	540	L	Multi-Speed
9	66	2706	2806	2986	650	60-65	540	L	Multi-Speed
10	72	2935	3035	3215	680	60-65	540	L	Multi-Speed
	4 5 5.5 6 6 7 7 8 8 9	Size Blades 4 30 5 36 5.5 42 6 42 6 48 7 48 7 54 8 54 8 60 9 66	Size Blades B to B (mm) 4 30 1188 5 36 1424 5.5 42 1585 6 42 1805 6 48 1805 7 48 2000 7 54 2000 8 54 2205 8 60 2205 9 66 2706	Size No. of Blades Working Width B to B (mm) width (mm) 4 30 1188 1288 5 36 1424 1524 5.5 42 1585 1685 6 42 1805 1905 6 48 1805 1905 7 48 2000 2100 7 54 2000 2100 8 54 2205 2305 8 60 2205 2305 9 66 2706 2806	Size No. of Blades Working Width B to B (mm) width (mm) width (mm) 4 30 1188 1288 1470 5 36 1424 1524 1705 5.5 42 1585 1685 1865 6 42 1805 1905 2085 7 48 2000 2100 2280 7 54 2000 2100 2280 8 54 2205 2305 2485 8 60 2205 2305 2485 9 66 2706 2806 2986	Size No. of Blades Working Width B to B (mm) width (mm) width (mm) Weight (kg) 4 30 1188 1288 1470 427 5 36 1424 1524 1705 450 5.5 42 1585 1685 1865 475 6 42 1805 1905 2085 480 6 48 1805 1905 2085 505 7 48 2000 2100 2280 530 7 54 2000 2100 2280 535 8 54 2205 2305 2485 560 8 60 2205 2305 2485 570 9 66 2706 2806 2986 650	Size No. of Blades Working Width B to B (mm) width (mm) width (mm) Weight (kg) Tractor hp 4 30 1188 1288 1470 427 30-35 5 36 1424 1524 1705 450 35-40 5.5 42 1585 1685 1865 475 40-45 6 42 1805 1905 2085 480 45-50 6 48 1805 1905 2085 505 45-50 7 48 2000 2100 2280 530 50-55 7 54 2000 2100 2280 535 50-55 8 54 2205 2305 2485 560 55-60 8 60 2205 2305 2485 570 55-60 9 66 2706 2806 2986 650 60-65	Size No. of Blades Working Width B to B (mm) width (mm) width (mm) Weight (kg) Tractor hp PTO (rpm) 4 30 1188 1288 1470 427 30-35 540 5 36 1424 1524 1705 450 35-40 540 5.5 42 1585 1685 1865 475 40-45 540 6 42 1805 1905 2085 480 45-50 540 7 48 2000 2100 2280 530 50-55 540 7 54 2000 2100 2280 535 50-55 540 8 54 2205 2305 2485 560 55-60 540 8 60 2205 2305 2485 570 55-60 540 9 66 2706 2806 2986 650 60-65 540	Size No. of Blades Working Width B to B (mm) width (mm) width (mm) Weight (kg) Tractor hp PTO (rpm) Blade Type 4 30 1188 1288 1470 427 30-35 540 L 5 36 1424 1524 1705 450 35-40 540 L 5.5 42 1585 1685 1865 475 40-45 540 L 6 42 1805 1905 2085 480 45-50 540 L 6 48 1805 1905 2085 505 45-50 540 L 7 48 2000 2100 2280 530 50-55 540 L 8 54 2205 2305 2485 560 55-60 540 L 8 60 2205 2305 2485 570 55-60 540 L 9 66 2706 2806



*Equipped with Mechanical seals: Ideal for Dry & Wet Land Operations



4 number of damper springs in 7 feet & above variants

DEALER / DISTRIBUTOR

*Available with H3+ Variant Only





Jagatjit Agri India Pvt. Ltd.Village Dehlon, Distirct Ludhiana, Punjab (141118)

Saron Mechanical Works

Mansa Road, Cheema Mandi, Sunam, Punjab (148029)